

A standard linear barcode is positioned vertically on the right side of the page. It is oriented such that the numbers above it correspond to the barcode's pattern.

ISSUE CLASSIFICATION

BEST AVAILABLE COPY

U.S. UTILITY Patent Application

O.I.P.E.	PATENT DATE
SCANNED <u>MS (3)</u> Q.A. <u>UR</u>	

APPLICATION NO. 09/733087	CONT/PRIOR F	CLASS 709	SUBCLASS 203	ART UNIT 2152 2143	EXAMINER <i>Renshaw</i>
------------------------------	-----------------	--------------	-----------------	--------------------------	----------------------------

PLICANTS Fumitaka Murayama

Method and system for providing character contents in the form of images

PTO-2040
12/99

ISSUING CLASSIFICATION

TERMINAL DISCLAIMER	DRAWINGS			CLAIMS ALLOWED	
	Sheets Drwg.	Figs. Drwg.	Print Fig.	Total Claims	Print Claim for O.G.
<input type="checkbox"/> The term of this patent subsequent to _____ (date) has been disclaimed.				NOTICE OF ALLOWANCE MAILED	
<input type="checkbox"/> The term of this patent shall not extend beyond the expiration date of U.S Patent. No. _____ _____				ISSUE FEE	
	(Primary Examiner)	(Date)		Amount Due	Date Paid
<input type="checkbox"/> The terminal _____ months of the term have been disclaimed.				ISSUE BATCH NUMBER	

WARNING:

The information disclosed herein may be restricted. Unauthorized disclosure may be prohibited by the United States Code Title 35, Sections 122, 181 and 368. Possession outside the U.S. Patent & Trademark Office is restricted to authorized employees and contractors only.

Form PTO-438A
(Rev. 6/99)

FILED WITH: DISK (CRF) FICHE CD-ROM
(Attached in pocket on right inside flap)